

MONDOTURF NSF MONOFIBRE STX 90 10 A SUPERCOURT

PADEL



Latest generation artificial turf, manufactured with the TUFTING system. It has a gauge of 3/16" with 28 tufts/dm, resulting in 58.800 tufts/m². The STx Supercourt blue or green turf filament has a height of 10 mm and 11.250 Dtex.

The filaments that make up the ST^X Supercourt system are equipped with a semi-concave and texturized structure in MONOFILAMENT with 250 µm thickness, lubricated with very low levels of abrasion. The filaments are made from polyethylene (PE) with specific additives that are characterized by high resistance to UV rays, to heat, to cold temperatures and extreme climatic variations.

The STx Supercourt filaments are connected to the backing thanks to the TUFTING system. The backing is made with double layer of polipropilene with a weight of 215 g/m². A peculiar characteristic of this support is the exceptional dimensional stability. After the process described above, approximately 600 g/m² of polyurethane are incorporated into the product via the finishing line. This operation fixes the filaments to the backing, obtaining a tear resistance of between 25 - 50 N. The total weight of the finished product is approximately 2.558 g/m² with a maximum roll width of 4 meters.

The lower layer is achieved during installation through a ballasting process made with rounded, washed and dried quartz sand granules. The sand has a 97% silicon content with a particle size between 0,2 - 0,6 mm, and is applied at a ratio of 12 Kg/m².

The MONDOTURF range of artificial grass systems has been developed to ensure excellent sporting and technical capabilities. The MONDOTURF artificial grass surface is installed on a level and evenly compacted surface. The laying and union of the rolls is made with polyurethane bi-component adhesive spread on the geotextile joints. The line marking for play are made with the same material.

The Mondoturf NSF Monofibre STX 90 10 A SUPERCOURT system is laboratory certified in accordance with **GREENGUARD / GREENGUARD GOLD, Producto Homologado FEP - Federación Española de Pádel.**

The system of artificial grass surfaces is manufactured in accordance with the UNE EN ISO 9001 quality management systems in regards to the design, development, production, marketing, installation and maintenance of the artificial grass surface. It was developed according to the I+D+i management system in accordance with the UNE 166002 standard relating to the research, development and innovation of textile technologies for artificial grass surfaces and synthetic fibre materials. Furthermore, it is manufactured in accordance with the UNE EN ISO 14001 quality and environmental management systems regarding the design, development, production, marketing, installation and maintenance of the artificial grass surface.

Carpet composition		Carpet Properties	
Yarn type:	Monofibre STX Supercourt (6 filaments)	Yarn dtex:	11.250 Dtex (± 10%)
Yarn Composition:	100% POLYETHYLENE	Yarn Thickness:	250 µm (± 10%)
Color:	Green, Blue	Yarn Height:	10 mm (± 5%)
Backing type:	2 layers/ 215 g/m ²	Sitches per linear dm:	28 tufts/dm
Backing Composition:	PP / PP	Stitches m ² :	58.800 tufts/m ² (± 10%)
Covering type:	Polyurethane (PU)	Number of filaments/m ² :	705.600
Tufting Process:	Line Tufting	Water Permeability:	≥ 500 mm/h (only outdoor courts)
Gauge:	3/16"	Maximum roll size:	20,45 x 4 m

Carpet Weights		Recommended Infills	
Yarn Weight:	1.743 g/m ² (± 10%)	Stabilizing Infill:	Quartz sand, rounded, washed and dried
Backing Weight:	215 g/m ² (± 5%)	Article size (range):	0,2 - 0,6 mm
Coating weight:	600 g/m ² (±10%)	Quantity:	12 Kg/m ²
Total weight:	2.558 g/m ² (±10%)		

06/11/2018

Mondo keeps the right to modify the characteristics of the products in any moment

www.mondoworldwide.com

